



Europäisches  
Patentamt

European  
Patent Office

Office européen  
des brevets

MAILED 24 JUN 2004

WIPO

PCT

PCT/IB 04/50956

Bescheinigung

Certificate

Attestation

Die angehefteten Unterlagen stimmen mit der ursprünglich eingereichten Fassung der auf dem nächsten Blatt bezeichneten europäischen Patentanmeldung überein.

The attached documents are exact copies of the European patent application described on the following page, as originally filed.

Les documents fixés à cette attestation sont conformes à la version initialement déposée de la demande de brevet européen spécifiée à la page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

03101876.5

**PRIORITY  
DOCUMENT**  
SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

Der Präsident des Europäischen Patentamts;  
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets  
p.o.

R C van Dijk



Anmeldung Nr:  
Application no.: 03101876.5  
Demande no:

Anmeldetag:  
Date of filing: 25.06.03  
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

Philips Intellectual Property & Standards  
GmbH  
Steindamm 94  
20099 Hamburg  
ALLEMAGNE  
Koninklijke Philips Electronics N.V.  
Groenewoudseweg 1  
5621 BA Eindhoven  
PAYS-BAS

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:  
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.  
If no title is shown please refer to the description.  
Si aucun titre n'est indiqué se référer à la description.)

A method of decentralized medium access control in a communication network

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s)  
revendiquée(s)  
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/  
Classification internationale des brevets:

H04L12/28

Am Anmeldetag benannte Vertragstaaten/Contracting states designated at date of  
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LU MC NL  
PT RO SE SI SK TR LI

**DESCRIPTION**

**A method of decentralized medium access control in a communications network**

**The invention relates to a method of decentralized medium access control in a communications network consisting of a plurality of stations.**

5

**Wireless local area networks (WLANs) based on Institute of Electronics and Electrical Engineering (IEEE) 802.11 constantly conquer new markets, the home user market being the most important of them all. Despite WLANs in business use, a home WLAN will not offer infrastructure for the network. Therefore, all centralized support for**  
10 **Quality of Service (QoS) is of lower importance than in the business network. A decentralized support for QoS is needed.**

**In decentralized WLANs, no co-ordination instance can reserve the wireless medium for time bounded services. Co-ordination functions as the EDCF of 802.11e work on a**  
15 **probability driven basis, such that there is still the possibility of collisions on the wireless medium, not only between traffic derived from sources of the same priority, but also from different priorities. These collisions reduce the throughput as they generate overhead and increase the delay. For periodic real time traffic like VoIP it may even be unacceptable to tolerate this delay.**

20

**To the satisfaction of the home user, a new co-ordination function regarding multihop connections is needed. It shall combine multihop capability with the support for Quality of Service. Existing co-ordination functions for 802.11 are not useful for multihop connections, since they are designed for single hop connections only.**

25

**Therefore it is the object of the invention to overcome the disadvantages of the standard 802.11 collision avoidances and to propose a method of decentralized medium access control to reserve the wireless medium to the needs of Quality of Service applications.**

This object is solved by a method as defined in claim 1 and a communications network as defined in claim 13.

According to the invention, a method of decentralized medium access control in a  
5 communications network consisting of a plurality of stations offers that a sending  
station transmits a reservation request for a future transmission to an intended receiving  
station, said intended station being in a reception range of said sending station, said  
reservation request signalling reservation information including starting point and duration  
of the transmission, defining a time period of said future transmission, and, in case of a  
10 multi-channel system, frequency or code of the channel of said future transmission, so  
establishing a reservation, and stations active in said reception range overhear said  
reservation request and other stations than said intended receiving station perform the  
actions of storing said reservation information locally and defer from medium access  
during the time period and on the channel of the future transmission.

15 The invention foresees that stations which are planning a data transmission, announce the  
starting point in time, duration of the transmission and eventually even the frequency or  
code channel in a reservation packet. This reservation packet is overheard by the other  
stations in the reception range of the sending station of the reservation request. The other  
20 stations store this information and defer from any medium access at the announced point  
in time on the respective frequency code channel and for the duration of the planned  
transmission.

In a preferred embodiment, said intended receiving station acknowledges said reservation  
25 request by returning a message repeating said reservation information, and other stations  
than the intended receiving station active in the reception range for transmissions of said  
receiving station perform the actions of storing said reservation information locally and  
defer from medium access during the time period and on the channel of the future  
transmission upon overhearing said acknowledgement message. Thereby, in order to clear  
30 the medium also on the receiver side, the reservation packet is sent back by the intended  
receiving station, when it is received from the sending station. By these means, the other  
stations in the reception range of the intended receiving station are informed about the

planned transmission of the sending station and can also defer from any medium access during the announced period.

5 The overhead of the reservation mechanism can be reduced by transmitting the reservation request piggy-back to normal data frames. Also said acknowledgement message can be transmitted piggy-back in an acknowledgement frame of a data packet or another data packet.

10 In a further preferred embodiment, the reservation request includes information on the priority or priority class of the future transmission, said priority information being used in that active stations in said reception range of said sending station replace an existing reservation information stored for the respective time period by new reservation information of a most recently received reservation request, if the existing reservation request has a lower priority than the most recently received reservation request; and the  
15 station that has been previously allocated the channel for the respective time period withdraws or delays its future transmission, if the most recently received reservation has a higher priority.

Also, when the acknowledgement message includes information on the priority or priority  
20 class of the future transmission, the priority information is used in that active stations in the reception range of that receiving station replace an existing reservation information as explained above.

According to the decentralized nature of the new protocol different reservations may  
25 overlap or stations may wish to transmit at the same time. Therefore, a reservation collision resolvance algorithm is needed. Each station which desires to reserve an interval is to check existent reservation entries in its local table. As each reservation belongs to a certain priority, the station checks the priority of its own reservation request against the colliding reservation. If it has lower priority, the station has to defer  
30 its reservation request. This step may be repeated until a slot is found which fits the desired length of the stations own reservation duration. In case of reservation requests of the same priority, the older reservation request may be given higher priority.

In a preferred embodiment, several periodic transmissions can be signalled by a single reservation request, and a time period derived from reservation information of a reservation request of a first future transmission being interpreted as period also of the following future transmissions and stations active in the reception range overhear said reservation request and other stations than said intended receiving station perform the actions of storing said reservation information locally and defer from medium access during all signalled time periods on all respective channels of the future transmissions.

The signalled starting point of the future transmission can be defined relatively to the beginning or end of the sending time or the beginning or end of the time slot of said reservation request, so that no global synchronization of clocks is required.

Correspondingly, when the starting point of the future transmission signalled in the acknowledgement message will be defined relatively to the beginning or end of the sending time or the beginning or end of the time slot as a time base of said acknowledgement message, the starting point information from the sending station is adapted to the time base of said acknowledgement message.

Collisions of reservation requests can be resolved by a collision resolution mechanism, for example, a reservation request of shorter duration of transmission can replace an existing reservation of longer duration of transmission, or reservation information of a most recent reservation request replaces an existing reservation, if the most recent reservation request has an earlier due time than the existing information.

If a reservation request is to be revoked, the sending station transmits a revocation message to said intended receiving station for the purpose of deleting one or several of its reservation requests; and stations active in the reception range for transmissions of said sending station overhear said revocation message and other stations than said intended receiving station locally delete the corresponding reservation information. The intended receiving station can then acknowledge said revocation message by returning a message repeating said revocation information; and other stations than the intended receiving station active in the reception range for transmissions of said receiving station

perform the actions of locally deleting the reservation information corresponding to the revocation information.

5 It may also be provided that a station broadcasts a copy of its locally stored reservation information; and stations active in the reception range for transmissions of said station compare the received reservation information with their locally stored information and add missing reservations to their locally stored reservation information.

10 The invention also relates to a communications network consisting of a plurality of stations, wherein the method as described herein is used.

The invention will be further explained in detail with reference to the accompanying drawings, wherein

15 **Figure 1** shows an example how the distributed reservation can be embedded in the frame structure of the IEEE 802.11 system; and

**Figure 2** shows an example of the data frame exchange including a reservation request.

20

In figure 1, the reservation information is included in the frame body. Alternatively, the reservation information could also be included in the frame header. The reservation information consists of the following fields:

- 25
- period of the traffic
  - duration of the medium reservation
  - priority of data transmission
  - number of future reservation periods.

30

The period of the traffic informs other stations when the next frame will be transmitted. The duration field informs other stations about the duration of the next data transmission of this stream, including time for the acknowledgement message. The priority field includes information about the traffic category this stream belongs to. By designating the priority of the future transmission, it is possible to support different Quality of Service levels in the network. In case that two transmissions are planned for the same time period, the higher priority traffic will gain the medium access and the lower priority sending station will automatically withdraw or delay its reservation.

- 10 An optional field informs other stations about the number of future reservation periods to be made. This allows a station to make a periodic reservation by a single reservation packet. The period between two transmissions is given in the "period of traffic" field, and the constant duration of each transmission in the "duration of the medium reservation" field.

15

As shown in figure 2, station (STA) A transmits a frame to station B. The data frame also includes a reservation request. Station C and station D overhear this data transmission and copy the reservation request information. Thus they can set up a table of reservation requests. As already mentioned above, the receiving station will

- 20 optionally repeat the reservation information in its acknowledgement message for the purpose of dealing with the hidden station problem. This acknowledgement message can be received by stations which are hidden to the sender and therefore might interfere during the reserved duration as they are in the reception range of the receiver but out of the reception range of the sending station.

25

With every overheard or received reservation request, every station updates its internal reservation request table, includes the most recently received reservation requests and eventually replaces an already stored reservation in case that the new reservation has a higher priority.

30



As different stations may independently chose different reservation periods and reservation duration, a collision avoidance mechanism is needed. First of all, the priority of the reservation request has to be considered. Stations requesting a reservation for a lower priority stream delay to higher priority streams. Stations requesting a reservation of the same priority may chose strategies like "shortest job first" or "first come, first serve" for collision avoidance. Conflicting reservation requests which partially overlap shall be reordered in the most efficient way. This may lead to increased delays for low priority streams, which must not delay VoIP frames etc. If still a reservation conflict occurs, the oldest reservation request shall be prioritised. New arriving reservation requests may not rule out old reservation requests.

Especially when every reservation request reserve only its succeeding frame, a revocation procedure for reservation requests is not generally needed. In case a large number reservation requests is made in advance, the next requested reservation may be used to transmit a revocation frame for the purpose of deleting reservation requests in other stations tables.

In addition to the reservation requests scheme described above, stations may also transmit their reservation request table in every beacon frame they generate. As all stations of an Independent Basic Service Set (IBSS) participate in the generation of a beacon frame, the station which generates the beacon frame may also transmit its local reservation request table inside the beacon to achieve a better synchronization of the reservation request table of all stations. This may also help to achieve a coherent reservation request table between partial overlapping Basic Service Sets (BSS).

According to the invention, using the reservation information, every station of the BSS can predict transmissions from neighbouring stations and refrain from channel access at the desired time. For the support of time bounded services, the protocol shall optionally allow a BSS wide etiquette that stations are not allowed to start any own transmission if the during of their own transmission does not end before the beginning of the

reservation. Therefore, the requested reservation will be safe from any delay. If this strict behaviour, which might decrease overall throughput, is not desired, the station which requested the reservation will become a 1-persistent station. It has highest priority then, as it will start its own transmission immediately after the ongoing  
5 transmission.

The invention avoids time consuming, delay increasing and throughput decreasing collisions on the wireless medium. Especially multihop connections will benefit from the protocol as it makes it possible to schedule transmissions and to behave more  
10 intelligent than just drawing a random number in trying to transmit after a random period. The benefit is the distribution of transmission intentions of neighbouring stations. This allows to further enhance the protocol by extensions which make use of the fact that the time of a future transmission is known.

CLAIMS

1. A method of decentralized medium access control in a communications network consisting of a plurality of stations, wherein
  - a sending station transmits a reservation request for a future transmission to an intended receiving station, said intended receiving station being in a reception range of said sending station, said reservation request signalling reservation information including starting point and duration of the transmission, defining a time period of said future transmission, and, in case of a multi-channel system, frequency or code of the channel of said future transmission, so establishing a reservation, and
  - stations active in said reception range overhear said reservation request and other stations than said intended receiving station perform the actions of storing said reservation information locally and defer from medium access during the time period and on the channel of the future transmission.
2. The method of claim 1, wherein
  - said intended receiving station acknowledges said reservation request by returning a message repeating said reservation information; and
  - other stations than the intended receiving station active in the reception range for transmissions of said receiving station perform the actions of storing said reservation information locally and defer from medium access during the time period and on the channel of the future transmission upon overhearing said acknowledgement message.
3. The method of claim 1, wherein said reservation request is transmitted piggy-back to a data packet in a frame or in another signalling frame.

4. The method of claim 3, wherein said acknowledgement message is transmitted piggy-back in an acknowledgement frame of said data packet or another data packet.
- 5
5. The method of claim 1, wherein said reservation request includes information on the priority or priority class of said future transmission, said priority information being used in that
- active stations in said reception range of said sending station replace an existing reservation information stored for the respective time period by new reservation information of a most recently received reservation request, if the existing reservation request has a lower priority than the most recently received reservation request; and
  - the station that has been previously allocated the channel for the respective time period withdraws or delays its future transmission, if the most recently received reservation has a higher priority.
- 10
- 15
6. The method of claim 1, wherein said acknowledgement message includes information on the priority or priority class of said future transmission, said priority information being used in that
- active stations in said reception range of said receiving station replace an existing reservation information stored for the respective time period by new reservation information of a most recently received reservation request, if the existing reservation request has a lower priority than the most recently received reservation request; and
  - that station that has been previously allocated the channel for the respective time period withdraws or delays its future transmission, if the most recently received reservation has a higher priority.
- 20
- 25
- 30

7. The method of claim 1 or 2, wherein several periodic transmissions are signalled by a single reservation request and
- a time period derived from reservation information of a reservation request of a first future transmission being interpreted as period also of the following future transmissions, and
  - stations active in said reception range overhear said reservation request and other stations than said intended receiving station perform the actions of storing said reservation information locally and defer from medium access during all signalled time periods on all respective channels of the future transmissions.
8. The method of claim 1, wherein the signalled starting point of said future transmission is defined relatively to a specific point in time associated with the reservation request message, like e.g. the beginning or end of the sending time or the beginning or end of the time slot of said reservation request, so that no global synchronization of clocks is required.
9. The method of claim 1, wherein said specific point in time, which serves as reference point for the definition of the starting time of the future transmission, is defined relatively to the beginning of the reservation request message and signalled inside the reservation request message.
10. The method of claim 2, wherein
- the starting point of the future transmission signalled in the acknowledgement message is defined relatively to the beginning or end of the sending time or the beginning or end of the time slot as a time base of said acknowledgement message and
  - adapting starting point information from said sending station to the time base of said acknowledgement message.

11. The method of claim 1, wherein collisions of reservation requests are resolved by a collision resolution mechanism.
- 5 12. The method of claim 1, wherein a reservation request of shorter duration of transmission replaces an existing reservation of longer duration of transmission.
13. The method of claim 1, wherein reservation information of a most recent reservation request replaces an existing reservation if the most recent reservation request has an earlier due time than the existing information.
- 10
14. The method of claim 1, wherein
- said sending station transmits a revocation message to said intended receiving station for the purpose of deleting one or several of its reservation requests; and
  - stations active in the reception range for transmissions of said sending station overhear said revocation message and other stations than said intended receiving station locally delete the corresponding reservation information.
- 15
- 20
15. The method of claim 1, wherein
- said intended receiving station acknowledges said revocation message by returning a message repeating said revocation information; and
  - other stations than the intended receiving station active in the reception range for transmissions of said receiving station perform the actions of locally deleting the reservation information corresponding to the revocation information.
- 25
- 30

16. The method of claim 1, wherein
- a station broadcasts a copy of its locally stored reservation information; and
  - stations active in the reception range for transmissions of said station compare the received reservation information with their locally stored information and add missing reservations to their locally stored reservation information.
17. A communications network consisting of a plurality of stations, including
- a sending station which transmits a reservation request for a future transmission to an intended receiving station, said intended receiving station being in a reception range of said sending station, said reservation request signalling reservation information including starting point and duration of the transmission, defining a time period of said future transmission, and, in case of a multi-channel system, frequency or code of the channel of said future transmission, so establishing a reservation, and
  - stations active in said reception range which overhear said reservation request, wherein other stations than said intended receiving station perform the actions of storing said reservation information locally and defer from medium access during the time period and on the channel of the future transmission.
18. The communications network of claim 17, characterized in that
- said intended receiving station acknowledges said reservation request by returning a message repeating said reservation information; and
  - other stations than the intended receiving station active in the reception range for transmissions of said receiving station perform the actions of storing said reservation information locally and defer from medium access during the time period and on the channel of the future transmission upon overhearing said acknowledgement message.

19. The communications network of claim 17, characterized in that said reservation request includes information on the priority or priority class of said future transmission, said priority information being used in that
- 5       - active stations in said reception range of said sending station replace an existing reservation information stored for the respective time period by new reservation information of a most recently received reservation request, if the existing reservation request has a lower priority than the most recently received reservation request; and
- 10       - the station that has been previously allocated the channel for the respective time period withdraws or delays its future transmission, if the most recently received reservation has a higher priority.
20. The communications network of claim 17, characterized in that said acknowledgement message includes information on the priority or priority class of said future transmission, said priority information being used in that
- 15       - active stations in said reception range of said receiving station replace an existing reservation information stored for the respective time period by new reservation information of a most recently received reservation request, if the existing reservation request has a lower priority than the most recently received reservation request; and
- 20       - that station that has been previously allocated the channel for the respective time period withdraws or delays its future transmission, if the most recently received reservation has a higher priority.
- 25
21. The communications network of claim 17, characterized in that several periodic transmissions are signalled by a single reservation request wherein a time period derived from reservation information of a reservation request of a first future transmission being interpreted as period also of the following future transmissions, and
- 30



- 5                   - stations active in said reception range overhear said reservation request and other stations than said intended receiving station perform the actions of storing said reservation information locally and defer from medium access during all signalled time periods on all respective channels of the future transmissions.
- 10           22.    The communications network of claim 17, characterized in that
- said sending station transmits a revocation message to said receiving station for the purpose of deleting one or several of its reservation requests; and
- stations active in the reception range for transmissions of said sending station overhear said revocation message and other stations than said intended receiving station locally delete the corresponding reservation information.
- 15           23.    The communications network of claim 17, characterized in that
- said intended receiving station acknowledges said revocation message by returning a message repeating said revocation information; and
- other stations than the intended receiving station active in the reception range for transmissions of said receiving station perform the actions of
- 20                   locally deleting the reservation information corresponding to the revocation information.
24.    The communications network of claim 17, characterized in that
- a station broadcasts a copy of its locally stored reservation information; and
- 25                   - stations active in the reception range for transmissions of said station compare the received reservation information with their locally stored information and add missing reservations to their locally stored reservation information.
- 30

**Abstract**

**A method of decentralized medium access control in a communications network**

**A method of decentralized medium access control in a communications network consisting of a plurality of stations, wherein**

- 5 a sending station transmits a reservation request for a future transmission to an intended receiving station, said intended receiving station being in a reception range of said sending station, said reservation request signalling reservation information including starting point and duration of the transmission, defining a time period of said future transmission, and, in case of a multi-channel system, frequency or code of the channel of said future**
- 10 transmission, so establishing a reservation, and**  
**stations active in said reception range overhear said reservation request and other stations than said intended receiving station perform the actions of storing said reservation information locally and defer from medium access during the time period and on the channel of the future transmission.**

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**